

102630

ShieldPRO CCT Tri Wattage

FEATURES

- 5 years (2 years + 3 years) extended warranty
- Matt white & clear acrylic finish (white bezel included)
- Constructed from steel & aluminium alloy & acrylic
- CCT switchable - Four colour temperature to choose from: Warm White (2700/3000K), Cool White (4000K) & Daylight White (6000K)
- Loop-in / Loop-out detachable quick wire push-fit connector
- 30, 60 and 90 minutes fire rated
- Tested with insulation cover thickness 300mm
- Suitable for bathroom zone 2
- Suitable for bathroom zone 1 if used in conjunction with a 30MA RCD
- IP65

SPEC DATA

Product Wattage:	4/6/8W
Product Lumen:	400/600/800
Lumen/W:	100
Kelvin:	2700/3000/4000/6000K
SDCM:	6
CRI:	80
Dimmable:	Yes
Lifetime (Hours):	30000
Beam Angle:	60°
Power Factor:	0.9
Driver Type:	Constant Current 120mA
Energy Rating:	E
Product Voltage:	220-240V
Hertz:	50/60
Surge Protection (KV):	1.5
Operating Temp.:	-20 to 40 Degree
Product Weight (KG):	0.2485
Cut-out:	Ø70mm
Minimum Cavity Depth:	48mm
Terminal Block:	Push-fit 6 ways
Class:	2

ACCESSORIES

- 90377, Satin nickel bezel
- 90378, Polished chrome bezel
- 92513, Matt black bezel
- 103944, EM conversion kit 8W
- 101345, Dimmer module 100W universal
- 101346, Dimmer module 250W trailing edge

