

102672

OrbitalPRO 4CCT

FEATURES

- 5 years (2 years + 3 years) extended warranty
- Matt white finish
- Constructed from die cast aluminium alloy & steel
- Fire rated to 30 minutes
- Tested with insulation cover thickness 270mm
- Suitable for bathroom zone 2
- Suitable for bathroom zone 1 if used in conjunction with a 30MA RCD
- IP65
- No visible light source
- Fits into shallow spaces
- Anti-glare indirect light source creating a stylish clean look

SPEC DATA

Product Wattage:	15W
Product Lumen:	1100
Lumen/W:	73
Kelvin:	2700/3000/4000/6000K
SDCM:	6
CRI:	80
Dimmable:	Yes
Lifetime (Hours):	30000
Beam Angle:	130°
Power Factor:	0.9
Driver Type:	Constant Current 250mA
Energy Rating:	E
Product Voltage:	220-240V
Hertz:	50/60
Surge Protection (KV):	1.5
Operating Temp.:	-20 to 40 Degree
Product Weight (KG):	0.481
Cut-out (mm):	Ø155mm
Minimum Cavity Depth (mm):	56mm
Terminal Block:	3 way Quick fit
Class:	2

ACCESSORIES

- 92514, Emergency LED conversion kit
- 101339, EM Conversation ST
- 101345, Dimmer module 100W universal
- 101346, Dimmer module 250W trailing edge

