


ERROR | DOWNLIGHT | BLACK

2015650103

nordlux®



Voltage (V): 220-240 Volt
IP degree: IP65
Class (Class 1, Class 2, Class 3):
Class 2 (Double isolated)
Bulb base: LED Module
Parallel connection: True

Primary material: Plastic
Secondary material: Metal
Suitable for Seaside: No
Color: Black

Height (cm): 7
Projection (cm): 5.4
Built In Spot Diameter (cm): 7.2
Mount directly into insulation:
False

EAN: 5704924003059
TUN: 2116039
Item Number: 2015650103
Pcs Per Master Carton: 6

Sales Box Height (cm): 13
Sales Box Width(cm): 13
Sales Box Depth (cm): 7
Sales Box Volume m³ : 0.0012
Product net weight (kg): 0.112

Brightness of light (Lumen): 360
Color Temperature (K): 2200-6500
Ra-value : 80
Lifetime (h): 20000
Beam Angle (°) : 36
Candela (cd) (for directional lamp only): 0
Energy Class: F
Actual Watt (W): 4.7

- IP 65 protection for both outdoor and bathroom use • Bluetooth connection to Nordlux Smart Light
- Adjustable kelvin and lumen output

Dorado Smart Light is simple and modern downlight which has a high degree of protection, IP65, making it suitable for both outdoor and bathroom use. Using the integrated Nordlux Smart Light function allows you to control the light from your selected device.

The Dorado downlight is integrated with the newest Bluetooth Mesh technology allowing you to easily manage the light setting using your selected device. No matter whether you are inside or outside the Bluetooth will allow for a stable communication between your light and device.

www.nordlux.com

ENERG

Nordlux
2015650103

A
B
C
D
E
F
G

5 kWh/1000h

2019/2015