

# ERROR | DOWNLIGHT | BRUSHED NICKEL

2015650155

nordlux®



Voltage (V): 220-240 Volt

IP degree: IP65

Class (Class 1, Class 2, Class 3):

Class 2 (Double isolated)

Bulb base: LED Module

Parallel connection: True

Primary material: Plastic

Secondary material: Metal

Suitable for Seaside: No

Color: Brushed Nickel

Height (cm): 7

Projection (cm): 5.4

Built In Spot Diameter (cm): 7.2

Mount directly into insulation:

False

EAN: 5704924003066

TUN: 2116063

Item Number: 2015650155

Pcs Per Master Carton: 6

Sales Box Height (cm): 13

Sales Box Width(cm): 13

Sales Box Depth (cm): 7

Sales Box Volume m<sup>3</sup> : 0.0012

Product net weight (kg): 0.112

Brightness of light (Lumen): 360

Color Temperature (K): 2200-6500

Ra-value : 80


Lifetime (h): 20000

Beam Angle (°) : 36

Candela (cd) (for directional lamp only): 0

Energy Class: F

Actual Watt (W): 4.7



- IP 65 protection for both outdoor and bathroom use • Bluetooth connection to Nordlux Smart Light
- Adjustable kelvin and lumen output

Dorado Smart Light is simple and modern downlight which has a high degree of protection, IP65, making it suitable for both outdoor and bathroom use. Using the integrated Nordlux Smart Light function allows you to control the light from your selected device.

The Dorado downlight is integrated with the newest Bluetooth Mesh technology allowing you to easily manage the light setting using your selected device. No matter whether you are inside or outside the Bluetooth will allow for a stable communication between your light and device.

[www.nordlux.com](http://www.nordlux.com)