

LEONIS 3-KIT 4000K | DOWNLIGHT | WHITE

49200101

nordlux[®]

Voltage (V): 230 Volt
IP degree: IP65
Class (Class 1, Class 2, Class 3):
Class 2 (Double isolated)
Bulb base: LED Module
Dimmerable: False
Parallel connection: True

Built In Spot Diameter (cm): 8.5
EAN: 5701581467187
TUN: 2298482
Item Number: 49200101

Pcs Per Master Carton: 3
Sales Box Height (cm): 13
Sales Box Width(cm): 13
Sales Box Depth (cm): 9
Sales Box Volume m³ : 0.0015
Product net weight (kg): 0.23

Primary material: Plastic
Color: White

Brightness of light (Lumen): 400
Color Temperature (K): 4000
Ra-value : 80
Lifetime (h): 20000
Beam Angle (°) : 360
Energy Class: F

Leonis is a single downlight with a low installation height. The downlight has an integrated LED and a frame in white plastic which contributes to a long life and low energy consumption. Furthermore, the downlight has opal white diffuser glass, that allows light to spread beautifully throughout the room. It is quick and easy to install Leonis via a screwless plug-in connection and twist-lock system. In addition, the downlight has a flexible cutting diameter (Ø68-73/76mm) and allows for parallel connection.

The high degree of protection, IP65, makes Leonis highly suitable for e.g. the bathroom, as it will tolerate a humid environment. Leonis also emits a practical and functional white light of 4000 K, which is particularly useful in for example the kitchen or hallway, where there is often a need for good work light.

