

52409

Xeno Triple

FEATURES

- 2 years warranty
- Aluminium finish
- Constructed from die cast aluminium alloy
- 355° rotation and 30° tilt

SPEC DATA

Product Wattage:	3 x Max. 50W GU10 (required)
Dimmable:	Y
Product Voltage:	220-240V
IP Rating:	20
Product Weight (KG):	0.573
Terminal Block:	2-way
Class:	2
Cut Hole:	79 x 258mm
Minimum Cavity Depth:	150mm

ACCESSORIES

70257, GU10 LED 60°, 3000K
70258, GU10 LED 60°, 4000K
74045, GU10 LED 60°, 6000K
70259, GU10 LED dimmable 60°, 3000K
70260, GU10 LED dimmable 60°, 4000K
74048, GU10 LED dimmable 60°, 6000K
78859, GU10 LED SMD 38°, 3000K
78860, GU10 LED SMD 38°, 4000K
78861, GU10 LED SMD 38°, 6000K
78862, GU10 LED SMD dimmable 38°, 3000K
78863, GU10 LED SMD dimmable 38°, 4000K
78864, GU10 LED SMD dimmable 38°, 6000K
90631, GU10 LED SMD 38°, 3000K
90632, GU10 LED SMD 38°, 4000K
90982, GU10 LED SMD dimmable 38°, 3000K
90983, GU10 LED SMD dimmable 38°, 4000K

