

69881 OrbitalPLUS

FEATURES

- 5 years (2 years + 3 years) extended warranty
- Constructed from die cast aluminium alloy & steel
- Satin nickel finish
- Anti-glare indirect light source creating a stylish clean look
- Fire rated to 30, 60 & 90 minutes
- IP65. Suitable for bathroom zone 2
- Suitable for bathroom zone 1 if used in conjunction with a 30MA RCD
- Can be covered with insulation

SPEC DATA

Product Wattage:	9W
Product Lumen:	460
Lumen/W:	51
Kelvin:	3000K
Energy Rating:	E
Dimmable:	Yes
Beam Angle:	120°
CRI:	80
Lifetime (Hours):	30000
LED Type:	SMD
SDCM:	<6
Driver Type:	Constant current 200mA
Product Voltage:	220-240V
Hertz:	50/60
IP Rating:	65
Operating Temp:	-20 to 40 Degree
Cut out:	Ø97mm
Minimum Cavity Depth:	43mm
Product Weight (KG):	0.215
Terminal Block:	3-way fast fix
Class:	2

ACCESSORIES

- 92514, Emergency LED conversion kit
- 101339, EM Conversation ST
- 101345, Dimmer module 100W universal
- 101346, Dimmer module 250W trailing edge

