

81026

Stratus UGR<19

FEATURES

- 3 years (2 years + 1 year) extended warranty
- White & opal plastic finish
- Constructed from aluminium alloy & steel & polystyrene
- IP40
- UGR<19
- TPB rated
- For use in T-bar ceilings

SPEC DATA

Product Wattage:	40W
Product Lumen:	3720
Lumen/W:	93
Kelvin:	4000K
SDCM:	≤ 4
CRI:	> 80
Dimmable:	N
Lifetime (Hours):	50000
Beam Angle:	120°
Power Factor:	> 0.9
UGR:	< 19
Driver Type:	Constant Current 1000mA
Energy Rating:	E
Product Voltage:	220-240V
Operational Voltage:	25-40V DC
Hertz:	50/60
Surge Protection (KV):	1.5
Operating Temp.:	-20 to 40 Degree
IK Rating:	03
Product Weight (KG):	1.94
Class:	3

ACCESSORIES

- 81007, LED driver constant current dimmable 40W 950mA
- 81744, Stratus suspension kit
- 81850, Stratus surface mount kit
- 91237, Recess clip
- 92514, Emergency LED conversion kit
- 92544, LED driver constant current 25/30/35/40W selectable
- 98449, LED driver constant current dimmable 40/50W
- 101339, EM conversation ST

