92274 StratusPRO TPA 6000K

FEATURES

- 5 years (2 years + 3 years) extended warranty
- White paint & opal plastic finish
- Constructed from aluminium alloy & steel & polystyrene
- IP40
- TPA rated
- For use in T-bar ceilings

SPEC DATA

Product Wattage:	40W
Product Lumen:	4000
Lumen/W:	100
Kelvin:	6000K
SDCM:	<5
CRI:	>80
Dimmable:	>00 N
Lifetime (Hours):	50000
Beam Angle:	110°
Power Factor:	0.9
Driver Type:	Constant C
Inrush Current at Start Up:	≤27A
Energy Rating:	E
Product Voltage:	220-240V
Operational Voltage:	33-40V D0
Hertz:	50/60
Surge Protection (KV):	1.5
Operating Temp.:	-20 to 40 I
IK Rating:	03
•	1.3
Product Weight (KG):	
Class:	3

6000K <5 >80N 50000 110° 0.9Constant Current 1000mA $\leq 27A$ E 220-240V 33-40V DC 50/60 1.5 -20 to 40 Degree 03 1.33

ACCESSORIES

81007, LED driver constant current dimmable 40W 950mA 81744, Stratus suspension kit 81850, Stratus surface mount kit 91237, Recess clip 92514, Emergency LED conversion kit 92544, LED driver constant current 25/30/35/40W selectable 92724, LED driver constant current 48W 1200mA 98449, LED driver constant current dimmable 40/50W 101339, EM conversation ST





