StratusPRO TPA 3000/4000/6000K

FEATURES

- 5 years (2 years + 3 years) extended warranty
- · White paint & opal plastic finish
- · Constructed from aluminium alloy & steel & polystyrene
- IP40
- TPA rated
- For use in T-bar ceilings



SPEC DATA

Product Wattage: 40W Product Lumen: 4000 Lumen/W: 100

Kelvin: 3000/4000/6000K


SDCM: <5
CRI: >80
Dimmable: N
Lifetime (Hours): 50000
Beam Angle: 110°
Power Factor: 0.9

Driver Type: Constant Current 1000mA

Inrush Current at Start Up: ≤27A
Energy Rating: E
Product Voltage: 220-240V
Operational Voltage: 33-40V DC
Hertz: 50/60
Surge Protection (KV): 1.5

Surge Protection (KV): 1.5
Operating Temp.: -20 to 40 Degree

IK Rating: 03
Product Weight (KG): 1.73
Class: 3



ACCESSORIES

81007, LED driver constant current dimmable 40W 950mA

81744, Stratus suspension kit

81850, Stratus surface mount kit

91237, Recess clip

92514, Emergency LED conversion kit

92544, LED driver constant current 25/30/35/40W selectable

92724, LED driver constant current 48W 1200mA

98449, LED driver constant current dimmable 40/50W

101339, EM conversation ST

